

nifty

HR17 HYBRID 4x4

SELF PROPELLED ACCESS PLATFORM



17m (56ft)
Working height

9.3m (30ft 6in)
Unrestricted working
outreach at 225kg

**Proportional
Multi-Function Control**
Fast & precise operation

GVW Only 4,750kg
Lowest weight in its class

Superb Manoeuvrability
3.7m turning radius

**ToughCage with SiOPS®
as Standard**
Mult award-winning
operator protection

**Platform Rotation
& Fly-Boom**
Improved access to
applications

Hybrid Power
Versatile, fuel efficient &
environmentally conscious



niftylift.com



nifty HR17 HYBRID 4x4

The **Height Rider 17 (HR17) Hybrid Four-Wheel-Drive (4x4)** is one of a new generation of environmentally conscious work platforms from Niftylift. Combining advanced power-source technology with efficient 4x4, it delivers outstanding performance from a compact and low-weight design.

On Diesel, the **HR17's** revolutionary **Hybrid** system can automatically utilise its electric motor to boost power whenever needed. This allows the **HR17 Hybrid 4x4** to operate with a smaller engine, reducing fuel consumption and its exhaust purification system then further reduces CO/NOx, particulates, and noise emissions.

The **HR17 Hybrid 4x4** can also operate on battery alone, making it ideal for indoor, quiet or clean applications. **Diesel Re-Gen** recharges the batteries without a mains power source and a fast charge is achieved whenever the machine is idle and the engine is left running.

SAFETY FEATURES

- SiOPS®
- Automatic Fail-Safe Brakes
- Tilt Alarm
- Solid Tyres
- Powered Auxiliary Descent
- Manual Recovery with Hand Pump
- Dual Controls (Platform & Base)
- Lock Valves on all Hydraulic Cylinders
- Dual Harness Points
- CE Mark



The **HR17 Hybrid 4x4** also incorporates **ToughCage** and **SiOPS®** technologies. A tough impact resistant composite base and larger cross-section steel give the ToughCage strength and durability, while SiOPS® offers additional operator protection.





SPECIFICATIONS

Working Height	17m	56ft
Platform Height	15m	49ft 6in
Working Outreach	9.3m	30ft 6in
Slew	360°	
Fly-Boom Arc	150°	
Width	2m	6ft 7in
Height	2.15m	7ft
Length - Stowed	5m	16ft 5in
- Overall	6.3m	20ft 8in
Minimum Weight	4,750kg*	10,500lbs*
Turning Radius - Outside	3.7m	12ft 2in
Platform Rotation	100°	
Platform Capacity	225kg	500lbs
Platform Size	1.8m x 0.85m	5ft 11in x 2ft 9in
Drive Speed - 4x4	5.5kmph	3.4mph
Gradeability	40% (22°)	
Hybrid Power System	Battery & Diesel (Kubota 722 - 18Hp/14kW)	

* Weights may vary according to specification, please confirm before ordering.

Due to a policy of continuing development and improvement, Niftylift reserves the right to change any specification without notice. Please confirm exact specification before ordering.



Supplied by:

Manufacturers of trailer mounted, self propelled and vehicle mounted platforms.

NIFTYLIFT LTD
Fingle Drive
Stonebridge
Milton Keynes
MK13 0ER
England

www.niftylift.com

e.mail: info@niftylift.com

Tel.: +44 (0)1908 223456

Fax.: +44 (0)1908 312733

